

CXE Fixed Gas Detector

www.hwsensor.com

CXE combustible gas detector is mainly used in small restaurants, shopping malls, underground integrated pipe corridors and other environments where gas may leak. When the gas concentration in the environment exceeds the preset alarming value, the indicator will give an alarm. At the same time, it can output signals and drive valves and other equipment to protect the user's personal and property safety.

FEATURES

- · Compact design
- · Low power consumption
- · Stable transmission
- · Cost-effective.

APPLICATION

Applicable to 9 small places such as industrial and commercial small restaurants, snack bars, barber shops, bathrooms, small hospitals, shopping malls etc.



SPECIFICATIONS

Sensor type	Catalytic sensor	Cable entry	NPT1/2
Power	DC24V±6V	Dimensions	95mm x 106mm x 76.5mm
Electrical output	RS485 Power BUS	Ex grade	Ex d ⅢC T6 Gb / Ex tD A21 IP66 T80°C
Operating temperature	-40 ~ 70°C	State indication	Yellow-Fault, Red-Alarm, Green-Power
Closure material	Aluminum alloy	Extendable functions	Wireless: GPRS / NB-loT Temperature and humidity collection function
Relay capacity	3A@DC30V or 3A@AC250V		
Ingress protection	IP66		



汉威科技集团股份有限公司 Hanwei Electronics Group Corporation

ADD: No.169 Xuesong Road, National & High Tech Zone, Zhengzhou 450001, Henan, China P.C: 450001

www.hwsensor.com

TEL: 86-371-67169070 / 80 FAX: 86-371-67169090

E-mail: sales@hwsensor.com